SAFETY DATA SHEET UNFILLED EPOXY 1040B

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME:

UNFILLED EPOXY 1040B

EER1040B

PART No.:

SUPPLIER:

H K WENTWORTH PTY LIMITED P.O. BOX 339 BROOKVALE, NSW 2100 AUSTRALIA Tel: 02 9938 1566 Fax: 02 9938 1566

2. COMPOSITION/INFORMATION ON INGREDIENTS:

| NAME | | | CONTENT |
|-----------------------------------|-------------|--|---------|
| CAS No.: | EINECS Nr.: | CLASSIFICATION | |
| 4,4'-METHYLENEDIA | ANILINE | | 10-30 % |
| 101-77-9 | 202-974-4 | T ,N R-45, 39/23/24/25, 43, 48/20/21/22, 51/53 Carc2 Mut3 | |
| 4,4'-METHYLENEbis(2-ETHYLANILINE) | | | 30-60 % |
| 19900-65-3 | 243-420-1 | Xn ,N R-22, 40, 50/53 Carc3 | |

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Harmful if swallowed. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. May cause cancer. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Carcinogen Category 2. Mutagen Category 3.

HAZARDOUS SUBSTANCE: DANGEROUS GOODS

4. FIRST AID MEASURES:

INHALATION:Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get
medical attention if any discomfort continues.INGESTION:DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT
OR DRINK FLUIDS! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get
medical attention immediately!SKIN:Wash the skin immediately with soap and water. Get medical attention promptly if
symptoms occur after washing.EYES:Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash
eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15
minutes and get medical attention.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA:

HAZARDOUS COMBUSTION PRODUCTS:

Fire creates: Vapors/gases/fumes of: Nitrous gases (NOx). Ammonia or amines. Carbon monoxide (CO).

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

6. ACCIDENTAL RELEASE MEASURES:

| Absorb in vermiculite, dry sand or earth and place into containers. Wear necessary |
|--|
| protective equipment. Stop leak if possible without risk. DO NOT touch spilled material. |

7. HANDLING AND STORAGE:

| USAGE PRECAUTIONS: | Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. |
|----------------------|--|
| STORAGE PRECAUTIONS: | Keep in cool, dry, ventilated storage and closed containers. Keep in original container. |

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

| INGREDIENT NAME: 4,4'-METHYLENEDIANILINE | CAS No.: 101-77-9 | STD MEL | LT EXP 8 Hrs 0.08 mg/m3 | ST EXP 15 Min |
|---|---|------------|-----------------------------------|---------------|
| INGREDIENT COMMENTS: | MEL = Maximum Exposure Limit. OES = Occupational Exposure Standard. | | | |
| PROTECTIVE EQUIPMENT: | | | | |



| VENTILATION: | Provide adequate general and local exhaust ventilation. |
|--------------------------|--|
| RESPIRATORS: | No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL). |
| PROTECTIVE GLOVES: | Use protective gloves. |
| EYE PROTECTION: | Wear approved safety goggles. |
| OTHER PROTECTION: | Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. |
| HYGIENIC WORK PRACTICES: | DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. No eating or drinking while working with this material. |

9. PHYSICAL AND CHEMICAL PROPERTIES:

| APPEARANCE: | Liquid. | | |
|-------------------------------------|------------------------|-------------------|------------------|
| COLOUR: | Brown. | | |
| DENSITY/SPECIFIC GRAVITY (g/ml): | 1.08 | Temperature (°C): | 20 |
| VISCOSITY (interval): | 1500 mPas | Temperature (°C): | 20 |
| SOLUBILITY DESCRIPTION: | Immiscible with water. | | |
| FLASH POINT (°C): | 91 | Method: | CC (Closed cup). |

10. STABILITY AND REACTIVITY:

| STABILITY: | Normally stable. |
|--------------------------------|--|
| CONDITIONS TO AVOID: | Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers. |
| HAZARDOUS DECOMP. PRODUCTS: | Fire creates: Acrid smoke/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Ammonia or amines. Nitrous gases (NOx). |

11. TOXICOLOGICAL INFORMATION:

| Toxicological data | LD50. Rabbit. 1000 mg/kg |
|--------------------------|---|
| TOXIC DOSE - LD 50: | 874 mg/kg (oral rat) |
| HEALTH HAZARDS, GENERAL: | Known or suspected carcinogen for humans. |
| INHALATION: | Toxic: danger of very serious irreversible effects through inhalation. |
| INGESTION: | Toxic: danger of very serious irreversible effects if swallowed. |
| SKIN: | Toxic: danger of very serious irreversible effects in contact with skin. May cause sensitisation by skin contact. |
| EYES: | May cause severe irritation to eyes. |
| HEALTH WARNINGS: | Known or suspected carcinogen for humans. Inhalation may cause: Irritation of nose and throat. |

12. ECOLOGICAL INFORMATION:

| ECOLOGICAL INFORMATION: | Dangerous for the environment if discharged into watercourses. |
|-------------------------|--|
|-------------------------|--|

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS:

Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION:

| UN No. ROAD: | 2810 |
|--------------------------|--------------------------------|
| UK ROAD TRANSPORT CLASS: | 6.1 |
| UK ROAD PACK GR.: | III |
| ADR CLASS No.: | 6.1 |
| ADR CLASS: | Division 6.1:Toxic substances. |
| ADR ITEM No.: | III |
| ADR LABEL No.: | 6.1 |
| HAZCHEM CODE: | 2X |
| CEFIC TEC(R) No.: | 61GT1-III |
| PROPER SHIPPING NAME I: | TOXIC LIQUID, ORGANIC, N.O.S. |
| RID CLASS No.: | 6.1 |

| RID ITEM No.: | Ш |
|-----------------|-----------|
| UN No. SEA: | 2810 |
| IMDG CLASS: | 6.1 |
| IMDG PACK GR.: | Ш |
| EmS No.: | F-A; S-A |
| MFAG TABLE No.: | See Guide |
| UN No., AIR: | 2810 |
| ICAO CLASS: | 6.1 |
| AIR PACK GR.: | Ш |
| | |

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



| RISK PHRASES: | R-22 Harmful if swallowed. R-39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R-40 Limited evidence of a carcinogenic effect. R-43 May cause sensitisation by skin contact. R-45 May cause cancer. R-48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. R-50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
|----------------------------|---|
| SAFETY PHRASES: | P-11 Restricted to professional users. S-27 Take off immediately all contaminated clothing. S-36/37 Wear suitable protective clothing and gloves. S-38 In case of insufficient ventilation, wear suitable respiratory equipment. S-45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). S-53 Avoid exposure - obtain special instructions before use. |
| ENVIRONMENTAL LISTING: | Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980. |
| EU DIRECTIVES: | System of specific information relating to Dangerous Preparations. 91\155. Dangerous Substance Directive 67\548. Dangerous Preparations Directive 88\379. |
| STATUTORY INSTRUMENTS: | Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health. |
| APPROVED CODE OF PRACTICE: | Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations L62. |
| GUIDANCE NOTES: | Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108). |

16. OTHER INFORMATION:

| USER NOTES: | CN No 39073000 |
|---------------------------|--|
| REVISION COMMENTS: | Revised in accordance with CHIP3 and EU Directive 1999/45/EC |
| ISSUED BY: | Helen O'Reilly |

| REVISION DATE: | MAY 2003 |
|-------------------------------|---|
| REV. No./REPL. SDS GENERATED: | 0 |
| SDS No.: | 10310 |
| DISCLAIMER: | This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification |
| R-PHRASES (Full Text): | R-45 May cause cancer. R-39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R-43 May cause sensitisation by skin contact. R-48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-22 Harmful if swallowed. R-40 Limited evidence of a carcinogenic effect. R-50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |