SAFETY DATA SHEET EPOXY RESIN 2123B

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: EPOXY RESIN 2123B

PART No.: EER2123B

SUPPLIER: H K WENTWORTH PTY LIMITED

P.O. BOX 339

BROOKVALE, NSW 2100

AUSTRALIA Tel: 02 9938 1566 Fax: 02 9938 1566

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME CONTENT

CAS No.: EINECS Nr.: CLASSIFICATION

4,4'-METHYLENEbis(2-ETHYLANILINE)

19900-65-3 243-420-1 Xn ,N R-22, 40, 50/53 Carc3

4,4'-METHYLENEDIANILINE 10-30 %

101-77-9 202-974-4 T ,N R-45, 39/23/24/25, 43, 48/20/21/22, 51/53 Carc2

Mut3

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Harmful if swallowed. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. Limited evidence of a carcinogenic effect. May cause sensitisation by skin contact. May cause cancer. Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Carcinogen Category 2. Mutagen Category 3.

30-60 %

HAZARDOUS SUBSTANCE: DANGEROUS GOODS

4. FIRST AID MEASURES:

INHALATION: Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get

medical attention if any discomfort continues.

INGESTION: DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT

OR DRINK FLUIDS! Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get

medical attention immediately!

SKIN: Wash the skin immediately with soap and water. Get medical attention promptly if

symptoms occur after washing.

EYES: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash

eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15

minutes and get medical attention.

5. FIRE FIGHTING MEASURES:

REVISION DATE: MAY 2003 10204 - EPOXY RESIN 2123B

EXTINGUISHING MEDIA: Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc.

HAZARDOUS COMBUSTION

Fire creates: Vapors/gases/fumes of: Nitrous gases (NOx). Ammonia or amines.

PRODUCTS:

Carbon monoxide (CO).

ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS: Absorb in vermiculite, dry sand or earth and place into containers. Wear necessary

protective equipment. Stop leak if possible without risk. DO NOT touch spilled material.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame.

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is

above accepted level.

STORAGE PRECAUTIONS: Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME: CAS No.: **STD** LT EXP 8 Hrs ST EXP 15 Min

4,4'-METHYLENEDIANILINE 101-77-9 MEL 0.08 mg/m3

INGREDIENT COMMENTS: MEL = Maximum Exposure Limit. OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:





VENTILATION: Provide adequate general and local exhaust ventilation.

RESPIRATORS: No specific recommendation made, but respiratory protection must be used if the

general level exceeds the Occupational Exposure Level (OEL).

PROTECTIVE GLOVES: Use protective gloves.

EYE PROTECTION: Wear approved safety goggles.

OTHER PROTECTION: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

HYGIENIC WORK PRACTICES: DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before

eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. No eating or

drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Liquid.

COLOUR: Brown.

(g/ml):

DENSITY/SPECIFIC GRAVITY 1.07 Temperature (°C): 25

VISCOSITY (interval): 18 Ps Temperature (°C): 25

10. STABILITY AND REACTIVITY:

STABILITY: Normally stable.

CONDITIONS TO AVOID: Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidisers.

HAZARDOUS DECOMP. Fire creates: Acrid smoke/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

PRODUCTS: Ammonia or amines. Nitrous gases (NOx).

11. TOXICOLOGICAL INFORMATION:

Toxicological data LD50. Rabbit. 1000 mg/kg

TOXIC DOSE - LD 50: 874 mg/kg (oral rat)

INHALATION: Toxic: danger of very serious irreversible effects through inhalation.

INGESTION: Toxic: danger of very serious irreversible effects if swallowed.

SKIN: Toxic: danger of very serious irreversible effects in contact with skin. May cause

sensitisation by skin contact.

EYES: May cause severe irritation to eyes.

HEALTH WARNINGS: Known or suspected carcinogen for humans. Inhalation may cause: Irritation of nose

and throat.

OTHER HEALTH EFFECTS: Carcinogen Category 2. Mutagen Category 3.

12. ECOLOGICAL INFORMATION:

ECOLOGICAL INFORMATION: Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS: Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION:

UN No. ROAD: 2810

UK ROAD TRANSPORT CLASS: 6.1

UK ROAD PACK GR.:

ADR CLASS No.: 6.1

ADR CLASS: Division 6.1:Toxic substances.

ADR ITEM No.:

ADR LABEL No.: 6.1

HAZCHEM CODE: 2X

CEFIC TEC(R) No.: 61GT1-III

PROPER SHIPPING NAME I: TOXIC LIQUID, ORGANIC, N.O.S.

RID CLASS No.: 6.1

RID ITEM No.:

UN No. SEA: 2810

IMDG CLASS: 6.1

IMDG PACK GR.:

EmS No.: F-A; S-A

MFAG TABLE No.: See Guide

UN No., AIR: 2810

ICAO CLASS: 6.1

AIR PACK GR.:

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:





RISK PHRASES: R-22 Harmful if swallowed.

R-39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in

contact with skin and if swallowed.

R-40 Limited evidence of a carcinogenic effect. R-43 May cause sensitisation by skin contact.

R-45 May cause cancer.

R-48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure

through inhalation, in contact with skin and if swallowed.

R-50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

SAFETY PHRASES: P-11 Restricted to professional users.

S-36/37 Wear suitable protective clothing and gloves.

S-38 In case of insufficient ventilation, wear suitable respiratory equipment.

S-45 In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

S-53 Avoid exposure - obtain special instructions before use.

ENVIRONMENTAL LISTING: Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste

Regulations) Act 1980.

EU DIRECTIVES: System of specific information relating to Dangerous Preparations. 91\155. Dangerous

Substance Directive 67\548. Dangerous Preparations Directive 88\379.

STATUTORY INSTRUMENTS: Chemicals (Hazard Information and Packaging) Regulations. Control of Substances

Hazardous to Health.

APPROVED CODE OF PRACTICE: Classification and Labelling of Substances and Preparations Dangerous for Supply.

Safety Data Sheets for Substances and Preparations L62.

GUIDANCE NOTES: Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation

HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

REVISION COMMENTS: Revised in accordance with CHIP3 and EU Directive 1999/45/EC

ISSUED BY: Helen O'Reilly

REVISION DATE: MAY 2003

REV. No./REPL. SDS GENERATED: 0

SDS No.: 10204

DISCLAIMER:This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless

specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or

quality specification

R-PHRASES (Full Text):

R-45 May cause cancer. R-39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R-43 May cause sensitisation by skin contact. R-48/20/21/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-22 Harmful if swallowed. R-40 Limited evidence of a carcinogenic effect. R-50/53 Very toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.