SAFETY DATA SHEET ONE PART DIPPING EPOXY

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME:

ONE PART DIPPING EPOXY

PART No.: EER2136

SUPPLIER:

H K WENTWORTH NZ LIMITED PO BOX 104-129 LINCOLN NORTH; HENDERSON AUCKLAND 1008 Tel: 64(0)9-836-65-88 Fax: 61(0)9-836-91-69

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME			CONTENT
CAS No.: NEOPENTYL GLYC	EINECS Nr.: OL DIGLYCIDYL ETI	CLASSIFICATION HER	10-30 %
17557-23-2	241-536-7	Xi R-38, 43	
Aliphatic Amines			10-30 %
·		Xi R-36/37	
EPOXY RESIN (Nun 25068-38-6	nber average MW <= 500-033-5	700) Xi ,N R-36/38, 43, 51/53	60-100 %

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

HAZARDOUS SUBSTANCE: DANGEROUS GOODS

4. FIRST AID MEASURES:

INHALATION:	Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.
INGESTION:	DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Promptly get affected personnel to drink large volumes of water to dilute the swallowed chemical. Get medical attention immediately!
SKIN:	Rinse the skin immediately with lots of water. Get medical attention if any discomfort continues.
EYES:	Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5. FIRE FIGHTING MEASURES:

```
EXTINGUISHING MEDIA:
```

Fire can be extinguished using: Foam. Alcohol resistant foam. Dry chemicals, sand,

SPECIAL FIRE FIGHTING **PROCEDURES:**

Use water to keep fire exposed containers cool and disperse vapours.

6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS:	Absorb in vermiculite, dry sand or earth and place into containers. Wear necessary protective equipment. Wash thoroughly after dealing with a spillage.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. **STORAGE PRECAUTIONS:** Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT COMMENTS: PROTECTIVE EQUIPMENT:

OES = Occupational Exposure Standard.



VENTILATION:	Provide adequate general and local exhaust ventilation.
RESPIRATORS:	No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL).
PROTECTIVE GLOVES:	Use protective gloves.
EYE PROTECTION:	Use approved safety goggles or face shield.
OTHER PROTECTION:	Wear appropriate clothing to prevent any possibility of skin contact.
HYGIENIC WORK PRACTICES:	DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE:	Paste or slurry.		
COLOUR:	Blue.		
BOILING POINT (°C, interval):	>200	Pressure:	
DENSITY/SPECIFIC GRAVITY (g/ml):	1.16	Temperature (°C):	20
VISCOSITY (interval):	145,000 mPas	Temperature (°C):	20
SOLUBILITY DESCRIPTION:	Insoluble in water.		
FLASH POINT (°C):	>200	Method:	CC (Closed cup).

10. STABILITY AND REACTIVITY:

STABILITY:	Normally stable.
CONDITIONS TO AVOID:	Avoid contact with acids and oxidising substances.
HAZARDOUS DECOMP. PRODUCTS:	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous gases (NOx).

11. TOXICOLOGICAL INFORMATION:

INHALATION:	No specific health warnings noted.
INGESTION:	May cause stomach pain or vomiting.
SKIN:	Irritating to skin. May cause allergic contact eczema. May cause sensitisation by skin contact.
EYES:	Irritating to eyes.
HEALTH WARNINGS:	EYES, NOSE AND MOUTH. Repeated exposure may cause chronic eye irritation. SKIN. Mild dermatitis, allergic skin rash. Defatting, drying and cracking of skin.
ROUTE OF ENTRY:	Ingestion. Skin and/or eye contact.

12. ECOLOGICAL INFORMATION:

LC 50, 96 HRS, FISH mg/l:	1.2
EC 50, 48 HRS, DAPHNIA, mg/l:	2.7
IC 50, 72 HRS, ALGAE, mg/l:	9.4
ECOLOGICAL INFORMATION:	Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS:

Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION:

LABEL FOR CONVEYANCE:



9
ш
9
Class 9: Miscellaneous dangerous substances and articles.

ADR ITEM No.:	III
ADR LABEL No.:	9
HAZCHEM CODE:	2X
CEFIC TEC(R) No.:	90GM6-III
PROPER SHIPPING NAME I:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (Number average MW <= 700))
RID CLASS No.:	9
RID ITEM No.:	III
UN No. SEA:	3082
IMDG CLASS:	9
IMDG PACK GR.:	III
EmS No.:	None
MFAG TABLE No.:	See Guide
MARINE POLLUTANT:	No.
UN No., AIR:	3082
ICAO CLASS:	9
AIR PACK GR.:	III

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES:	R-36/38 Irritating to eyes and skin. R-43 May cause sensitisation by skin contact. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SAFETY PHRASES:	S-24/25 Avoid contact with skin and eyes. S-26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S-37 Wear suitable gloves.
STATUTORY INSTRUMENTS:	Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

USER NOTES:	CN No 39073000
REVISION COMMENTS:	Revised in accordance with CHIP3 and EU Directive 1999/45/EC
ISSUED BY:	Helen O'Reilly
REVISION DATE:	MAY 2003

REV. No./REPL. SDS GENERATED:	0
SDS No.:	10286
DISCLAIMER:	This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification
R-PHRASES (Full Text):	R-36/38 Irritating to eyes and skin. R-43 May cause sensitisation by skin contact. R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R-38 Irritating to skin. R-36/37 Irritating to eyes and respiratory system.