# SAFETY DATA SHEET GRAFFITTI REMOVER GEL

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

**PRODUCT NAME:** GRAFFITTI REMOVER GEL

PART No.: EGRG400

**SUPPLIER**: H K WENTWORTH PTY LIMITED

P.O. BOX 339

**BROOKVALE, NSW 2100** 

AUSTRALIA Tel: 02 9938 1566 Fax: 02 9938 1566

## 2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME			CONTENT
CAS No.: 1-METHOXY-2-PROP	EINECS Nr.: Panol	CLASSIFICATION	30-60 %
107-98-2	203-539-1	- R-10	
DISTILLATES (PETR 64742-47-8	OLEUM), HYDROTR 265-149-8	REATED LIGHT; KEROSINE - UNSPECIFIED  Xn R-65	10-30 %
N-METHYL-2-PYRROLIDONE			5-10 %
872-50-4	212-828-1	Xi R-36/38	
BUTANE	000 440 7	5 D 40	10-30 %
106-97-8	203-448-7	Fx R-12	

The Full Text for all R-Phrases are Displayed in Section 16

## 3. HAZARDS IDENTIFICATION:

Irritating to eyes and skin.

HAZARDOUS SUBSTANCE: DANGEROUS GOODS

## 4. FIRST AID MEASURES:

**INHALATION:** Move the exposed person to fresh air at once. Provide rest, warmth and fresh air.

**INGESTION:** Not relevant.

**SKIN:** Wash the skin immediately with soap and water. Get medical attention if any discomfort

continues.

**EYES:** Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash

eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

## 5. FIRE FIGHTING MEASURES:

**EXTINGUISHING MEDIA:** Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

**SPECIAL FIRE FIGHTING** 

PROCEDURES:

Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapours.

**UNUSUAL FIRE & EXPLOSION** 

**HAZARDS**:

Aerosol cans may explode in fires.

## 6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS: Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

#### 7. HANDLING AND STORAGE:

**USAGE PRECAUTIONS:** Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is

above accepted level.

**STORAGE PRECAUTIONS:** Aerosol cans: Must not be exposed for direct sunlight or temperatures above 50°C.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT NAME: CAS No.: **STD** LT EXP 8 Hrs ST EXP 15 Min **BUTANE** 106-97-8 **OES** mag 000 750 ppm 1-METHOXY-2-PROPANOL 107-98-2 **OES** 100 ppm(Sk) 150 ppm(Sk) N-METHYL-2-PYRROLIDONE 872-50-4 **OES** 25 ppm(Sk) 75 ppm(Sk)

INGREDIENT COMMENTS: OES = Occupational Exposure Standard. MEL = Maximum Exposure Limit.

**VENTILATION:** All handling to take place in well ventilated area.

**RESPIRATORS:** No specific recommendation made, but respiratory protection must be used if the

general level exceeds the Occupational Exposure Level (OEL).

**PROTECTIVE GLOVES:** Use protective gloves.

**EYE PROTECTION:** Use eye protection.

OTHER PROTECTION: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

HYGIENIC WORK PRACTICES: DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before

eating, smoking and using the toilet. No eating or drinking while working with this

material.

## 9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Aerosol. Liquid.

COLOUR: Colourless.

ODOUR/TASTE: Characteristic.

**SOLUBILITY DESCRIPTION:** Insoluble in water.

FLASH POINT (°C): <0 Method: CC (Closed cup).

AUTO IGNITION TEMP. (°C): >250

FLAMMABILITY LIMIT - LOWER(%): 0.8

FLAMMABILITY LIMIT - UPPER(%): 13

## 10. STABILITY AND REACTIVITY:

STABILITY: Normally stable.

**CONDITIONS TO AVOID:** Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising

agents. Strong alkalis. Strong mineral acids.

HAZARDOUS DECOMP.

PRODUCTS:

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

## 11. TOXICOLOGICAL INFORMATION:

**HEALTH HAZARDS, GENERAL:** No specific health warnings noted.

**INHALATION:** Solvent vapours are hazardous and may cause nausea, sickness and headaches.

**INGESTION:** May cause discomfort if swallowed.

**SKIN:** Irritating to skin. Product has a defatting effect on skin. Prolonged or repeated contact

leads to drying of skin.

**EYES:** Irritating to eyes.

## 12. ECOLOGICAL INFORMATION:

**ECOLOGICAL INFORMATION:** Not regarded as dangerous for the environment.

## 13. DISPOSAL CONSIDERATIONS:

**DISPOSAL METHODS:** Empty containers must not be burned because of explosion hazard. Dispose of in

accordance with Local Authority requirements.

# 14. TRANSPORT INFORMATION:

#### LABEL FOR CONVEYANCE:



**UN No. ROAD:** 1950

UK ROAD TRANSPORT CLASS: 2.1

UK ROAD PACK GR.: Not Applicable

ADR CLASS No.: 2.1

ADR CLASS: Division 2.1: Flammable gases.

ADR ITEM No.: Not Applicable

ADR MARGINAL: 2201

ADR LABEL No.: 2.1

HAZCHEM CODE: N/A

CEFIC TEC(R) No.: 20G5F

PROPER SHIPPING NAME I: AEROSOLS

RID CLASS No.: 2.1

RID ITEM No.: Not Applicable

**UN No. SEA:** 1950

IMDG PACK GR.: Not Applicable

2 1

EmS No.: F-D; S-U

MFAG TABLE No.: See Guide

MARINE POLLUTANT: No.

**UN No., AIR**: 1950

ICAO CLASS: 2.1

AIR SUB CLASS: N/A

AIR PACK GR.: Not Applicable

## 15. REGULATORY INFORMATION:

#### **LABEL FOR SUPPLY:**

IMDG CLASS:





RISK PHRASES: R-36/38 Irritating to eyes and skin.

SAFETY PHRASES: S-16 Keep away from sources of ignition - No Smoking.

S-23 Do not breathe gas/fumes/vapour/spray. S-24/25 Avoid contact with skin and eyes.

S-26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S-51 Use only in well ventilated areas.

SPECIAL PROVISIONS ON THE LABELLING OF AEROSOL DISPENSERS. Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Keep away from sources of ignition - No smoking.

Keep out of the reach of children.

APPROVED CODE OF PRACTICE: Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES: Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation

HS(G)37. CHIP for everyone HSG(108).

## 16. OTHER INFORMATION:

**USER NOTES:** CN No 34039990

REVISION COMMENTS: Revised in accordance with CHIP3 and EU Directive 1999/45/EC

ISSUED BY: Helen O'Reilly

REVISION DATE: MAY 2003

REV. No./REPL. SDS GENERATED: 0

**SDS No.:** 10299

**DISCLAIMER:** This information relates only to the specific material designated and may not be valid

for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for the safe handling, use, processing,

storage, transportation, disposal and release and is not to be considered a warranty or

quality specification

R-PHRASES (Full Text): R-12 Extremely flammable. R-10 Flammable. R-65 Harmful: may cause lung damage if

swallowed. R-36/38 Irritating to eyes and skin.