60-100 %

SAFETY DATA SHEET SUPASOLV

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY:

PRODUCT NAME: SUPASOLV

PART No.: ESSV29K

SUPPLIER: H K WENTWORTH PTY LIMITED

P.O. BOX 339

BROOKVALE, NSW 2100

AUSTRALIA Tel: 02 9938 1566 Fax: 02 9938 1566

2. COMPOSITION/INFORMATION ON INGREDIENTS:

NAME CONTENT

CAS No.: EINECS Nr.: CLASSIFICATION

1,1-DICHLORO-1-FLUOROETHANE

1717-00-6 404-080-1 N R-52/53, 59

The Full Text for all R-Phrases are Displayed in Section 16

3. HAZARDS IDENTIFICATION:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Dangerous for the ozone layer.

HAZARDOUS SUBSTANCE: NON DANGEROUS GOODS.

4. FIRST AID MEASURES:

INHALATION: Move the exposed person to fresh air at once. Keep the affected person warm and at

rest. Get prompt medical attention.

INGESTION: DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Get medical attention.

SKIN: Promptly wash contaminated skin with soap or mild detergent and water. Promptly

remove clothing if soaked through and wash as above. Get medical attention if irritation

persists after washing.

EYES: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash

eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES:

EXTINGUISHING MEDIA: This material is not flammable. Use extinguishing media appropriate for surrounding

fire.

6. ACCIDENTAL RELEASE MEASURES:

SPILL CLEANUP METHODS: Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of

water to clean spillage area.

7. HANDLING AND STORAGE:

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS: Keep in cool, dry, ventilated storage and closed containers. Keep in original container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION:

INGREDIENT COMMENTS: OES = Occupational Exposure Standard.

PROTECTIVE EQUIPMENT:





VENTILATION: Provide sufficient ventilation during operations which cause vapour formation.

RESPIRATORS:No specific recommendation made, but respiratory protection must be used if the

general level exceeds the Occupational Exposure Level (OEL).

PROTECTIVE GLOVES: Use protective gloves.

EYE PROTECTION: Wear approved chemical safety goggles where eye exposure is reasonably probable.

OTHER PROTECTION: Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

HYGIENIC WORK PRACTICES: DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before

eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes

20

contaminated. No eating or drinking while working with this material.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Liquid.

COLOUR: Colourless.

ODOUR/TASTE: Mild (or faint). Ether.

BOILING POINT (°C, interval): 32 Pressure:

MELT./FREEZ. POINT (°C, interval): 1970

DENSITY/SPECIFIC GRAVITY 1.240 Temperature (°C):

(g/ml):

SOLUBILITY DESCRIPTION: Insoluble in water.

10. STABILITY AND REACTIVITY:

STABILITY: Normally stable.

CONDITIONS TO AVOID: Not known.

11. TOXICOLOGICAL INFORMATION:

INGESTION: May cause stomach pain or vomiting.

HEALTH WARNINGS: No specific health warnings noted. No specific acute or chronic health impact noted,

but this chemical may still have adverse impact on human health, either in general or

on certain individuals with pre-existing or latent health problems.

OTHER HEALTH EFFECTS: This substance has no evidence of carcinogenic properties.

12. ECOLOGICAL INFORMATION:

LC 50, 96 HRS, FISH mg/l: >100

EC 50, 48 HRS, DAPHNIA, mg/l: 31

ECOLOGICAL INFORMATION: Dangerous for the environment if discharged into watercourses.

13. DISPOSAL CONSIDERATIONS:

DISPOSAL METHODS: Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION:

ADR CLASS: Not classified for transportation.

MARINE POLLUTANT: No.

15. REGULATORY INFORMATION:

LABEL FOR SUPPLY:



RISK PHRASES: R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R-59 Dangerous for the ozone layer.

SAFETY PHRASES: S-59 Refer to manufacturer/supplier for information on recovery/ recycling.

S-61 Avoid release to the environment. Refer to special instructions/ Safety Data

Sheets.

UK REGULATORY REFERENCES: Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid

Regulations 1972. Fire precautions Act 1971. Health and Safety at Work Act 1974. The

Control of Substances Hazardous to Health Regulations 1988.

ENVIRONMENTAL LISTING: Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste

Regulations) Act 1980. Control of Pollution Act 1974.

EU DIRECTIVES: System of specific information relating to Dangerous Preparations. 91\155. Dangerous

Substance Directive 67\548. Dangerous Preparations Directive 88\379.

STATUTORY INSTRUMENTS: Chemicals (Hazard Information and Packaging) Regulations. Control of Substances

Hazardous to Health.

APPROVED CODE OF PRACTICE: Classification and Labelling of Substances and Preparations Dangerous for Supply.

Safety Data Sheets for Substances and Preparations L62.

GUIDANCE NOTES: Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation

HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION:

REVISION COMMENTS: Revised in accordance with CHIP3 and EU Directive 1999/45/EC

ISSUED BY: Helen O'Reilly

REVISION DATE: DECEMBER 2003

REV. No./REPL. SDS GENERATED: 0

SDS No.: 10622

DISCLAIMER: This information relates only to the specific material designated and may not be valid

for such material used in combination with any other materials or in any process unless specified in the text. The information contained in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The

information given is designed only as guidance for the safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or

quality specification

R-PHRASES (Full Text): R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment. R-59 Dangerous for the ozone layer.